

X-ROAD TEAM COMP

MATTE TROOPER GREEN/CHROME/BLACK



ROAD & GRAVEL / GRAVEL

FRAME

FRAME

Carbon X-Road Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB865, SH dropout, Thru Axle 135x12 mm, Inner cable routing, Di2 compatible, mudguards ready

HEAD SET

ACROS AIX-525, 1-1/8"

FORK

X-Road Team Comp 28", Carbon rigid, Ahead 1-1/8x1.5", 12x100mm axle

DRIVETRAIN

CASSETTE

SunRace CS-MS7-11, 11-42T

BOTTOM BRACKET

SHIMANO BB-RS500 PressFit, shell 41x86.5mm

CHAIN

KMC X11

GEARS

1x11

REAR DERAILLEUR

SHIMANO GRX RD-RX810 Shadow Plus

CRANKSET

SHIMANO GRX FC-RX600, 40T

WHEELS

WHEELSET

DT Swiss G 1800 Spline DB25; 12x142mm, CENTER LOCK, Tubeless, DT Swiss G 1800 Spline DB25; 12x100mm, CENTER LOCK, Tubeless

TIRES

Schwalbe G-One Allround RaceGuard, 28x1.50"

WEIGHT

8.9kg

COMPONENTS

BRAKES

SHIMANO GRX ST-RX600/BR-RX400, hydraulic disc brake, SHIMANO GRX BL-RX600/BR-RX400, hydraulic disc brake

SADDLE

Selle Royal Seta Performa

SEAT POST

ONE1 Carbon, SP0225380AERO, 27x380mm

HANDLEBAR

ONE1 Alloy, X-Race Aero, 16° flared, 70mm rise, 420mm, 31.8mm

STEM

ONE1 TDS-660 Alloy, 31.8mm, 7°

GRIPS

ONE1 VL-T073, StickyGel

GEOMETRY

FRAME SIZE	52cm (S)	54cm (M)	56cm (L)	58cm (XL)
WHEEL SIZE	28	28	28	28
SEAT TUBE LENGTH (MM)	462	482	502	522
SEAT TUBE ANGLE (DEGREE)	73.8	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	531	544	568	590
REACH (MM)	376	379	392	408
STACK (MM)	536	557	578	597
HEAD TUBE LENGTH (MM)	120	140	160	180
HEAD TUBE ANGLE (DEGREE)	71	71.5	72	72
CHAINSTAY LENGTH (MM)	412	412	412	412
BB DROP (MM)	70	70	70	70
WHEELBASE (MM)	990	996	1010	1032
HANDLEBAR WIDTH (MM)	420	420	440	440
STEM LENGTH (MM)	80	90	100	110
CRANK LENGTH (MM)	172.5	172.5	175	175
SEAT POST LENGTH (MM)	380	380	380	380

*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city /country

SUPERIOR